

	SDR 41 PN 6			SDR 26 PN 10			
		, /	, /		, /	, /	
	90	2,8	97,08	90	4,3	142,14	
	110	2,7	114,95	110	4,2	177,01	
	160	4,0	247,69	160	6,2	369,81	
	225	5,5	478,95	225	8,6	730,23	
	315	7,7	946,53	315	12,1	1441,86	
	400	9,8	1590,48	400	15,3	2396,91	
	500	12,3	2509,70	500	19,1	3796,01	
	630	15,4	.				
		11°	22°	30°	45°	67°	90°
	90,00	179,22	191,58	197,76	238,55	296,64	302,20
	110,00	215,56	232,68	246,27	293,43	373,27	391,19
	160,00	517,51	578,45	609,60	700,19	924,53	1007,34
	225,00	1122,29	1270,61	1362,07	1676,70	2447,28	2505,37
	315,00	7341,84	8207,04	8837,40	10697,58	13596,02	14937,06
	400,00	20385,10	24354,14	27498,53	33782,35	43260,00	49563,60
500,00	58680,20	62343,84	64457,40	70946,40	80340 (60°)	91722,00	
							
	90		150,79	315		3614,68	
	110		202,02	400		11718,27	
	160		394,04	500		.	
225		804,45			.		
							
	90	1180,63	90 90 80/90°		1568,24		
	110	1202,01	110 110 80/90°		1783,05		
	160	1997,38	110 110 110/90°		1829,54		
	225	4208,58	160 160 80/90°		.		
315	6081,12	160 160 100/90°		3087,78			
							
	90	1006,41	160 160 150/90°		3587,49		
	110	1014,50	225 225 100/90°		5615,40		
	160	1493,10	225 225 150/90°		5615,60		
	225	2900,15	225 225 200/90°		6539,06		
315	4326,00						
				90		22,90	
				110		26,80	
				160		47,20	
90 90 90/90°		1800,85		225		84,05	
110 110 110/90°		2209,98		315		160,70	
160 160 110/90°		4845,12		400		343,60	
160 160 160/90°		5040,40		500		716,90	
225 225 110/90°		.					
225 225 160/90°		.					
225 225 225/90°		.					